

## Professional high-speed optical transceiver

**OPN-S8F15-80SC2 / OPN-S8F15-80SC2I / OPN-S8F15-80SC2-EMG /  
OPN-S8F15-80SC2I-EMG / OPN-S8F15-80ST2 / OPN-S8F15-80ST2I /  
OPN-S8F15-80FC2 / OPN-S8F15-80FC2I / OPN-S8F15T-80SC2 /  
OPN-S8F15T-80SC2I / OPN-S8F15T-80SC2-EMG /  
OPN-S8F15T-80SC2I-EMG / OPN-S8F15T-80ST2 / OPN-S8F15T-80ST2I /  
OPN-S8F15T-80FC2 / OPN-S8F15T-80FC2I  
3.3V / 1550 nm / 622 Mbps RoHS Compliant Optical Single-Mode Transceiver**

## PRODUCT FEATURES

- Duplex SC Single Mode Transceiver: OPN-S8F15-80SC2
- Duplex ST Single Mode Transceiver: OPN-S8F15-80ST2
- Duplex FC Single Mode Transceiver: OPN-S8F15-80FC2
- Long-Reach SONET OC-12 / SDH STM-4 (L-4.2)Compliant
  - 1550 nm DFB LD Transmitter
  - Industry Standard 1 x 9 Footprint
  - Single +3.3 V Power Supply
  - RoHS Compliant
- 0 to 70°C Operating: OPN-S8F15-80SC2-EMG
- -50 to 85°C Operating: OPN-S8F15-80SC2I-EMG
- PECL Signal Detect Output: OPN-S8F15-80SC2I-EMG
- TTL Signal Detect Output: OPN-S8F15T-80SC2I-EMG
- LED Multisourced 1 x 9 Transceiver Interchangeable
  - Wave Solderable
- Class 1 Laser International Safety Standard IEC 60825Compliant

## APPLICATIONS

- ATM 622 Mbps Links
- SONET / SDH Equipment Interconnect
- Fibre Channel 532 Mbps Links

## PRODUCT DESCRIPTION

The OPN-S8F15-80SC2I-EMG series single mode transceiver is a low power, high performance module for bi-directional serial optical data communications such as SONET OC-12 / SDH STM-4. This module is designed for single mode fiber and operates at a nominal wavelength of 1550 nm. The transmitter section uses a multiple quantum well 1550 nmDFB laser and is a class 1 laser compliant according to International Safety Standard IEC 60825. The receiver section uses an integrated InGaAs detector preamplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. A PECL logic interface simplifies interface to external circuitry.

## ORDER INFORMATION

| P/No.                | Bit Rate (Mb/s) | SONET / SDH | Distance (km) | Wavelength (nm) | Voltage (V) | Package      | Temp. (°C) | TX Power (dBm) | RX Sens. (dBm) | RoHS Compliant |
|----------------------|-----------------|-------------|---------------|-----------------|-------------|--------------|------------|----------------|----------------|----------------|
| OPN-S8F15-80SC2-EMG  | 622             | LR-2/L-4.2  | 80            | 1550 DFB        | 3.3         | 1X9 SC/ST/FC | 0 to 70    | 2 to -3        | -28            | Y              |
| OPN-S8F15-80SC2I-EMG | 622             | LR-2/L-4.2  | 80            | 1550 DFB        | 3.3         | 1X9 SC/ST/FC | -50 to 85  | 2 to -3        | -28            | Y              |

## Absolute Maximum Ratings

| Parameter             | Symbol | Min      | Max      | Units | Notes                                       |
|-----------------------|--------|----------|----------|-------|---------------------------------------------|
| Storage Temperature   | Tstg   | -50      | 85       | °C    |                                             |
| Operating Temperature | Topr   | 0<br>-50 | 70<br>85 | °C    | OPN-S8F15-80SC2-EMG<br>OPN-S8F15-80SC2I-EMG |
| Soldering Temperature | ---    |          | 260      | °C    | 10 seconds on leads only                    |
| Power Supply Voltage  | Vcc    | 0        | 3.6      | V     |                                             |
| Input Voltage         | ---    | GND      | Vcc      | V     |                                             |
| Output Current        | Iout   | 0        | 30       | mA    |                                             |

## Professional high-speed optical transceiver

| Recommended Operating Conditions |                  |          |     |          |                                                        |
|----------------------------------|------------------|----------|-----|----------|--------------------------------------------------------|
| Parameter                        | Symbol           | Min      | Typ | Max      | Units                                                  |
| Power Supply Voltage             | V <sub>CC</sub>  | 3.1      | 3.3 | 3.5      | V                                                      |
| Operating Temperature            | T <sub>opr</sub> | 0<br>-50 |     | 70<br>85 | °C / OPN-S8F15-80SC2I-EMG<br>°C / OPN-S8F15-80SC2I-EMG |
| Data Rate                        |                  | 50       | 622 |          | Mb/s                                                   |
| Power Supply Current             | I <sub>CC</sub>  |          |     | 260      | mA                                                     |

| Transmitter Specifications (0°C < T <sub>opr</sub> < 70°C, 3.1V < V <sub>CC</sub> < 3.5V) |                                                                    |      |      |       |       |                   |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------|------|------|-------|-------|-------------------|
| Parameter                                                                                 | Symbol                                                             | Min  | Typ  | Max   | Units | Notes             |
| <b>Optical</b>                                                                            |                                                                    |      |      |       |       |                   |
| Optical Transmit Power                                                                    | P <sub>o</sub>                                                     | -3   | ---  | 2     | dBm   | 1                 |
| Output Center Wavelength                                                                  | λ                                                                  | 1480 | 1550 | 1580  | nm    |                   |
| Output Spectrum Width                                                                     | Δλ                                                                 | ---  | ---  | 1     | nm    | -20 dB Width      |
| Side Mode Suppression Ratio                                                               | SMSR                                                               | 30   |      |       | dB    |                   |
| Extinction Ratio                                                                          | E <sub>R</sub>                                                     | 10   | ---  | ---   | dB    |                   |
| Output Eye                                                                                | Compliant with Bellcore TR-NWT-000253 and ITU recommendation G.957 |      |      |       |       |                   |
| Optical Rise Time                                                                         | t <sub>r</sub>                                                     |      |      | 1.2   | ns    | 10% to 90% Values |
| Optical Fall Time                                                                         | t <sub>f</sub>                                                     |      |      | 1.2   | ns    | 10% to 90% Values |
| Relative Intensity Noise                                                                  | RIN                                                                |      |      | -116  | dB/Hz |                   |
| Total Jitter                                                                              | TJ                                                                 |      |      | 0.55  | ns    | 2                 |
| <b>Electrical</b>                                                                         |                                                                    |      |      |       |       |                   |
| Data Input Current – Low                                                                  | I <sub>IL</sub>                                                    | -350 |      |       | μA    |                   |
| Data Input Current – High                                                                 | I <sub>IH</sub>                                                    |      |      | 350   | μA    |                   |
| Differential Input Voltage                                                                | V <sub>IH</sub> - V <sub>IL</sub>                                  | 300  |      |       | mV    |                   |
| Data Input Voltage – Low                                                                  | V <sub>IL</sub> - V <sub>CC</sub>                                  | -2.0 |      | -1.58 | V     | 3                 |
| Data Input Voltage -- High                                                                | V <sub>IH</sub> - V <sub>CC</sub>                                  | -1.1 |      | -0.74 | V     | 3                 |

Notes: 1. Output power is power coupled into a 9/125 μm single mode fiber.

2. Measured with a 2<sup>23</sup>-1 PRBS with 72 ones and 72 zeros.

3. These inputs are compatible with 10K, 10KH and 100K ECL and LVPECL inputs.

| Receiver Specifications (0°C < T <sub>opr</sub> < 70°C, 3.1V < V <sub>CC</sub> < 3.5V) |                                   |      |     |       |       |                         |
|----------------------------------------------------------------------------------------|-----------------------------------|------|-----|-------|-------|-------------------------|
| Parameter                                                                              | Symbol                            | Min  | Typ | Max   | Units | Notes                   |
| <b>Optical</b>                                                                         |                                   |      |     |       |       |                         |
| Sensitivity                                                                            | ---                               | ---  | --- | -28   | dBm   | 1                       |
| Maximum Input Power                                                                    | P <sub>in</sub>                   | -5   |     | ---   | dBm   |                         |
| Signal Detect -- Asserted                                                              | P <sub>a</sub>                    | ---  | --- | -28   | dBm   | Transition: low to high |
| Signal Detect -- Deasserted                                                            | P <sub>d</sub>                    | -40  | --- | ---   | dBm   | Transition: high to low |
| Signal detect -- Hysteresis                                                            |                                   | 1.0  | --- |       | dB    |                         |
| Wavelength of Operation                                                                |                                   | 1100 | --- | 1600  | nm    |                         |
| <b>Electrical</b>                                                                      |                                   |      |     |       |       |                         |
| Data Output Voltage – Low                                                              | V <sub>OL</sub> - V <sub>CC</sub> | -2.0 |     | -1.58 | V     | 2                       |
| Data Output Voltage – High                                                             | V <sub>OH</sub> - V <sub>CC</sub> | -1.1 |     | -0.74 | V     | 2                       |
| Signal Detect Output Voltage -- Low                                                    | V <sub>OL</sub> - V <sub>CC</sub> | -2.0 |     | -1.58 | V     | OPN-S8F15-80SC2I-EMG    |
| Signal Detect Output Voltage -- High                                                   | V <sub>OH</sub> - V <sub>CC</sub> | -1.1 |     | -0.74 | V     |                         |
| Signal Detect Output Voltage -- Low                                                    | V <sub>SDL</sub>                  |      |     | 0.8   | V     | OPN-S8F15T-80SC2I-EMG   |
| Signal Detect Output Voltage -- High                                                   | V <sub>SDH</sub>                  | 2.0  |     |       | V     |                         |

Notes: 1. Minimum sensitivity and saturation levels at BER=1E-10 for a 2<sup>23</sup>-1 PRBS with 72 ones and 72 zeros.

2. These outputs are compatible with 10K, 10KH and 100K ECL and LVPECL outputs.


## Professional high-speed optical transceiver

### CONNECTION DIAGRAM

|                           |            |          |
|---------------------------|------------|----------|
| Receiver Signal Ground    | 1 (Rx GND) |          |
| Receiver Data Out         | 2 (RD+)    | N/C      |
| Receiver Data Out Bar     | 3 (RD-)    |          |
| Signal Detect             | 4 (SD)     |          |
| Receiver Power Supply     | 5 (Rx Vcc) | TOP VIEW |
| Transmitter Power Supply  | 6 (Tx Vcc) |          |
| Transmitter Data In Bar   | 7 (TD-)    |          |
| Transmitter Data In       | 8 (TD+)    | N/C      |
| Transmitter Signal Ground | 9 (Tx GND) |          |

| PIN | Symbol | Notes                                                     |
|-----|--------|-----------------------------------------------------------|
| 1   | Rx GND | Directly connect this pin to the receiver ground plane    |
| 2   | RD+    | See recommended circuit schematic                         |
| 3   | RD-    | See recommended circuit schematic                         |
| 4   | SD     | Active high on this indicates a received optical signal   |
| 5   | Rx Vcc | +3.3V dc power for the receiver section                   |
| 6   | Tx Vcc | +3.3V dc power for the transmitter section                |
| 7   | TD-    | See recommended circuit schematic                         |
| 8   | TD+    | See recommended circuit schematic                         |
| 9   | Tx GND | Directly connect this pin to the transmitter ground plane |

### RECOMMENDED CIRCUIT SCHEMATIC




The split-load terminations for ECL signals need to be located at the input of devices receiving those ECL signals. The power supply filtering is required for good EMI performance. Use short tracks from the inductor L1/L2 to the module Rx Vcc and Tx Vcc. A GND plane under the module is required for good EMI and sensitivity performance.

## Professional high-speed optical transceiver

### PACKAGE DIAGRAM


Units in mm

#### 1) SC Type



OPN-S8F15-80SC2 / OPN-S8F15T-80SC2 /  
OPN-S8F15-80SC2I / OPN-S8F15T-80SC2I


#### 2) SC Type With Extended Shielding



OPN-S8F15-80SC2-EMG / OPN-S8F15T-80SC2-EMG /  
OPN-S8F15-80SC2I-EMG / OPN-S8F15T-80SC2I-EMG


## Professional high-speed optical transceiver

### 3) ST Type



OPN-S8F15-80ST2 / OPN-S8F15T-80ST2 /  
OPN-S8F15-80ST2I / OPN-S8F15T-80ST2I

### 4) FC Type



OPN-S8F15-80FC2 / OPN-S8F15T-80FC2 /  
OPN-S8F15-80FC2I / OPN-S8F15T-80FC2I

**Note:** Specifications subject to change without notice.