



Professional high-speed optical transceiver

OPN-S8G13-5D30SC / OPN-S8G13-5D30SCI
OPN-S8G13-5D30SC-EMG / OPN-S8G13-5D30SCI-EMG
OPN-S8G13-5D30ST / OPN-S8G13-5D30STI
OPN-S8G13-5D30FC / OPN-S8G13-5D30FCI
OPN-S8G13T-5D30SC / OPN-S8G13T-5D30SCI
OPN-S8G13T-5D30SC-EMG / OPN-S8G13T-5D30SCI-EMG
OPN-S8G13T-5D30ST / OPN-S8G13T-5D30STI
OPN-S8G13T-5D30FC / OPN-S8G13T-5D30FCI

5V / 1310 nm / 1.25 Gbps RoHS Compliant Optical Single-Mode Transceiver

PRODUCT FEATURES

- Duplex SC Single Mode Transceiver: OPN-S8G13-5D30SC
- Duplex ST Single Mode Transceiver: OPN-S8G13-5D30ST
- Duplex FC Single Mode Transceiver: OPN-S8G13-5D30FC
 - Compliant with IEEE 802.3z Gigabit Ethernet
 - Link Distance up to 30 km
 - Link Power Budget at Least 19 dB
 - Industry Standard 1 x 9 Footprint
 - 0 to 70°C Operating: OPN-S8G13-5D30FC
 - -50 to 85°C Operating: OPN-S8G13-5D30FCI
 - Single +5 V Power Supply
 - RoHS Compliant
- PECL Signal Detect Output: OPN-S8G13-5D30FC
- TTL Signal Detect Output: OPN-S8G13T-5D30FC
 - Wave Solderable
- Class 1 Laser International Safety Standard IEC 60825Compliant

APPLICATIONS

- Switch to Switch Interface
- High Speed Interface for File Servers
- High Performance Desktops

PRODUCT DESCRIPTION

The OPN-S8G13-5D30FC series single mode transceiver is a low power, high performance module for bi-directional serial optical data communications such Gigabit Ethernet andFibre Channel. This module is designed for single mode fiber and operates at a nominal wavelength of 1310 nm. Thetransmitter section uses a multiple quantum well laser and isa class 1 laser compliant according to International Safety Standard IEC 60825. The receiver section uses an integrated InGaAs detector preamplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. A PECLlogic interface simplifies interface to external circuitry.

ORDER INFORMATION

P/No.	Bit Rate (Mb/s)	1000 BASE	Distance (km)	Wavelength (nm)	Voltage (V)	Package	Temp. (°C)	TX Power (dBm)	RX Sens. (dBm)	RoHS Complia nt
OPN-S8G13-5D30FC	1250		30	1310	5	1X9 SC/ST/FC	0 to 70	0 to -5	-24	Y
OPN-S8G13-5D30FCI	1250		30	1310	5	1X9 SC/ST/FC	-50 to 85	0 to -5	-24	Y



Professional high-speed optical transceiver

Absolute Maximum Ratings					
Parameter	Symbol	Min	Max	Units	Notes
Storage Temperature	Tstg	-50	85	°C	
Operating Temperature	Topr	0 -50	70 85	°C	OPN-S8G13-5D30FC OPN-S8G13-5D30FCI
Soldering Temperature	---		260	°C	10 seconds on leads only
Power Supply Voltage	Vcc	0	6	V	
Input Voltage	---	GND	Vcc	V	
Output Current	Iout	0	30	mA	

Recommended Operating Conditions					
Parameter	Symbol	Min	Typ	Max	Units
Power Supply Voltage	Vcc	4.75	5	5.25	V
Operating Temperature	Topr	0 -50		70 85	°C / OPN-S8G13-5D30FC °C / OPN-S8G13-5D30FCI
Data Rate			1250	1300	Mb/s
Power Supply Current	Icc			270	mA

Transmitter Specifications (0°C < Topr < 70°C, 4.75V < Vcc < 5.25V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Optical Transmit Power	Po	-5	---	0	dBm	1
Output Center Wavelength	λ	1285	1310	1345	nm	
Output Spectrum Width	$\Delta\lambda$	---	1.8		nm	RMS(σ)
Extinction Ratio	ER		9	---	dB	
Output Eye	Compliant with IEEE 802.3z					
Optical Rise Time	t _r			0.26	ns	20% to 80% Values
Optical Fall Time	t _f			0.26	ns	20% to 80% Values
Relative Intensity Noise	RIN			-120	dB/Hz	
Total Jitter	TJ			0.227	ns	2
Electrical						
Data Input Current – Low	I _{IL}	-350			μA	
Data Input Current – High	I _{IH}			350	μA	
Differential Input Voltage	V _{IH} - V _{IL}	300			mV	
Data Input Voltage – Low	V _{IL} - V _{CC}	-2.0		-1.58	V	3
Data Input Voltage -- High	V _{IH} - V _{CC}	-1.1		-0.74	V	3

- Notes: 1. Output power is power coupled into a 9/125 μm single mode fiber.
 2. Measured with a 2⁷-1 PRBS.
 3. These inputs are compatible with 10K, 10KH and 100K ECL and LVPECL inputs.



Professional high-speed optical transceiver

Receiver Specifications (0°C < T _{opr} < 70°C, 4.75V < V _{cc} < 5.25V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Sensitivity	---	---	---	-24	dBm	1
Maximum Input Power	Pin	-3		---	dBm	
Signal Detect -- Asserted	Pa	---	---	-24	dBm	Transition: low to high
Signal Detect -- Deasserted	Pd	-50	---	---	dBm	Transition: high to low
Signal detect -- Hysteresis		1.0	---		dB	
Wavelength of Operation		1100	---	1600	nm	
Electrical						
Data Output Voltage -- Low	V _{OL} - V _{CC}	-2.0		-1.58	V	2
Data Output Voltage -- High	V _{OH} - V _{CC}	-1.1		-0.74	V	2
Signal Detect Output Voltage -- Low	V _{OL} - V _{CC}	-2.0		-1.58	V	OPN-S8G13-5D30FC
Signal Detect Output Voltage -- High	V _{OH} - V _{CC}	-1.1		-0.74	V	
Signal Detect Output Voltage -- Low	V _{SDL}			0.5	V	OPN-S8G13T-5D30FC
Signal Detect Output Voltage -- High	V _{SDH}	2.0			V	

Notes: 1. Minimum sensitivity and saturation levels at BER=1E-12 for a 2⁷-1 PRBS.


2. These outputs are compatible with 10K, 10KH and 100K ECL and PECL outputs.

CONNECTION DIAGRAM

Receiver Signal Ground	1 (Rx GND)	○
Receiver Data Out	2 (RD+)	N/C
Receiver Data Out Bar	3 (RD-)	
Signal Detect	4 (SD)	
Receiver Power Supply	5 (Rx Vcc)	TOP VIEW
Transmitter Power Supply	6 (Tx Vcc)	
Transmitter Data In Bar	7 (TD-)	
Transmitter Data In	8 (TD+)	N/C
Transmitter Signal Ground	9 (Tx GND)	○

PIN	Symbol	Notes
1	Rx GND	Directly connect this pin to the receiver ground plane
2	RD+	See recommended circuit schematic
3	RD-	See recommended circuit schematic
4	SD	Active high on this indicates a received optical signal
5	Rx Vcc	+5V dc power for the receiver section
6	Tx Vcc	+5V dc power for the transmitter section
7	TD-	See recommended circuit schematic
8	TD+	See recommended circuit schematic
9	Tx GND	Directly connect this pin to the transmitter ground plane

RECOMMENDED CIRCUIT SCHEMATIC




For TTL SD Level, R1=R2=N.C., R3=R5=82R, R4=R6=130R
For PECL SD Level, R1=R3=R5=82R, R2=R4=R6=130R

The split-load terminations for ECL signals need to be located at the input of devices receiving those ECL signals. The power supply filtering is required for good EMI performance. Use short tracks from the inductor L1/L2 to the module Rx Vcc and Tx Vcc. A GND plane under the module is required for good EMI and sensitivity performance.

PACKAGE DIAGRAM


Units in mm

1) SC Type With Extended Shielding



OPN-S8G13-5D30SC-EMG / OPN-S8G13T-5D30SC-EMG


2) ST Type



OPN-S8G13-5D30ST / OPN-S8G13T-5D30ST

Professional high-speed optical transceiver

3) FC Type



OPN-S8G13-5D30FC / OPN-S8G13T-5D30FC

Note: Specifications subject to change without notice.