

Professional high-speed optical transceiver

**OPN-S8G1314-40SC / OPN-S8G1314-40SCI / OPN-S8G1314T-40SC /
OPN-S8G1314T-40SCI / OPN-S8G1314P-40SC / OPN-S8G1314P-40SCI**

OPN-S8G1314TP-40SC / OPN-S8G1314TP-40SCI

1310 nm TX / 1490 nm RX , 3.3V / 1.25 Gb/s RoHS Compliant Single-Fiber Transceiver

PRODUCT FEATURES

- Bi-Directional Single-Fiber Transceiver
- Compliant with IEEE 802.3ah 1000BASE-BX
 - 1310 nm DFB LD Transmitter
 - 1490 nm Receiver
 - 1550 nm Enhanced Band Block
 - 20dB Power Budget At Least
 - Link distance up to 40 km
 - Industry Standard 1 x 9 Footprint
 - Single +3.3 V Power Supply
 - RoHS Compliant
- 0 to 70°C Operating: OPN-S8G1314-40SC
- -50 to 85°C Operating: OPN-S8G1314-40SCI
- LVPECL Differential Inputs and Outputs
- LVPECL Signal Detect Output : OPN-S8G1314-40SC
- LVTTTL Signal Detect Output : OPN-S8G1314T-40SC
 - Wave Solderable
- Class 1 Laser International Safety Standard IEC-60825Compliant

APPLICATIONS

- WDM 1.25 Gb/s Links
- SONET / SDH Equipment Interconnect
- Fiber Channel 1.063 Gb/s Links

PRODUCT DESCRIPTION

The OPN-S8G1314-40SC series are high performance modules for single fiber communications by using 1310 nm transmitter and 1490 nm receiver. This module is equipped with 3W-TRX™ OE device to reject 1.55 um high power video signal. The transmitter section uses a multiple quantum well 1310 nm DFB laser and is a class 1 laser compliant according to International Safety Standard IEC-60825. The receiver section is designed to receive 1490 nm and block 1550 nm signal. This feature is suitable for IEEE 802.3ah and ITU-T 983.3 application. The receiver section uses an integrated 1490 nm detector preamplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. A PECL logic interface simplifies interface to external circuitry.

ORDER INFORMATION

P/No.	1000 BASE	Bit Rate (Gb/s)	Distance (km)	TX (nm)	RX (nm)	Voltage (V)	Package	Temp.(°C)	TX Power (dBm)	RX Sens. (dBm)	RoHS Compliant
OPN-S8G1314-40SC	BX	1.25	40	1310 DFB	1490	3.3	1X9	0 to 70	2 to -3	-23	Yes
OPN-S8G1314-40SCI	BX	1.25	40	1310 DFB	1490	3.3	1X9	-50 to 85	2 to -3	-23	Yes
OPN-S8G1314T-40SC	BX	1.25	40	1310 DFB	1490	3.3	1X9	0 to 70	2 to -3	-23	Yes
OPN-S8G1314T-40SCI	BX	1.25	40	1310 DFB	1490	3.3	1X9	-50 to 85	2 to -3	-23	Yes
OPN-S8G1314P-40SC	BX	1.25	40	1310 DFB	1490	3.3	1X9	0 to 70	2 to -3	-23	Yes
OPN-S8G1314P-40SCI	BX	1.25	40	1310 DFB	1490	3.3	1X9	-50 to 85	2 to -3	-23	Yes
OPN-S8G1314TP-40SC	BX	1.25	40	1310 DFB	1490	3.3	1X9	0 to 70	2 to -3	-23	Yes
OPN-S8G1314TP-40SCI	BX	1.25	40	1310 DFB	1490	3.3	1X9	-50 to 85	2 to -3	-23	Yes

Professional high-speed optical transceiver

Absolute Maximum Ratings					
Parameter	Symbol	Min	Max	Units	Notes
Storage Temperature	Tstg	-50	85	°C	
Operating Temperature	Topr	0 -50	70 85	°C	OPN-S8G1314-40SC OPN-S8G1314-40SCI
Soldering Temperature	---		260	°C	10 seconds on leads only
Power Supply Voltage	Vcc	0	3.6	V	
Input Voltage	---	GND	Vcc	V	
Output Current	Iout	0	30	mA	

Recommended Operating Conditions					
Parameter	Symbol	Min	Typ	Max	Units / Notes
Power Supply Voltage	Vcc	3.13	3.3	3.47	V
Operating Temperature	Topr	0 -50		70 85	°C / OPN-S8G1314-40SC °C / OPN-S8G1314-40SCI
Data Rate			1250	1300	Mb/s
Power Supply Current	Icc			280	mA

Transmitter Specifications (0°C < Topr < 70°C, 3.13V < Vcc < 3.47V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Optical Transmit Power	Po	-3	---	2	dBm	1
Output Center Wavelength	λ	1260		1360	nm	
Output Spectrum Width	$\Delta\lambda$	---	---	1	nm	-20dB Width
Side Mode Suppression Ratio	SMSR	30			dB	
Extinction Ratio	ER	9.0	---	---	dB	
Output Eye	Compliant with IEEE 802.3z					
Optical Rise Time	t _r			0.26	ns	20% to 80% Values
Optical Fall Time	t _f			0.26	ns	20% to 80% Values
Relative Intensity Noise	RIN			-120	dB/Hz	
Total Jitter	TJ			0.227	ns	2
Electrical						
Data Input Current – Low	I _{IL}	-350			μA	
Data Input Current – High	I _{IH}			350	μA	
Differential Input Voltage	V _{IH} - V _{IL}	300			mV	
Data Input Voltage – Low	V _{IL} - V _{CC}	-2.0		-1.58	V	3
Data Input Voltage -- High	V _{IH} - V _{CC}	-1.1		-0.74	V	3

Notes: 1. Output power is power coupled into a 9/125 μm single mode fiber.

2. Measured with a 2⁷-1 PRBS.

3. These inputs are compatible with 10K, 10KH and 100K ECL and LVPECL inputs.

Professional high-speed optical transceiver

Receiver Specifications (0°C < Topr < 70°C, 3.13V < Vcc < 3.47V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Sensitivity	---	---	---	-23	dBm	1
Maximum Input Power	Pin	-3		---	dBm	
Signal Detect -- Asserted	Pa	---	---	-23	dBm	Transition: low to high
Signal Detect -- Deasserted	Pd	-40	---	---	dBm	Transition: high to low
Signal detect -- Hysteresis		1.0	---		dB	
Wavelength of Operation		1480	---	1500	nm	2,3
Optical Return Loss	ORL	14			dB	
Electrical						
Data Output Voltage -- Low	$V_{OL} - V_{CC}$	-2.0		-1.58	V	4
Data Output Voltage -- High	$V_{OH} - V_{CC}$	-1.1		-0.74	V	4
SD Output Voltage -- Low	$V_{OL} - V_{CC}$	-2.0		-1.58	V	OPN-S8G1314-40SC
SD Output Voltage -- High	$V_{OH} - V_{CC}$	-1.1		-0.74	V	
SD Output Voltage -- Low	V_{OL}	0		0.8	V	OPN-S8G1314T-40SC
SD Output Voltage -- High	V_{OH}	2.0		$V_{CC} + 0.3$	V	

Notes: 1. Minimum sensitivity and saturation levels at BER=1E-12 for a 2⁷-1 PRBS.

2. At least 30 dB optical isolation for the wavelength 1260 to 1360 nm.

3. At least 30 dB optical isolation for the wavelength 1550 to 1580 nm.

4. These outputs are compatible with 10K, 10KH and 100K ECL and LVPECL outputs.

CONNECTION DIAGRAM

Receiver Signal Ground
Receiver Data Out
Receiver Data Out Bar
Signal Detect
Receiver Power Supply
Transmitter Power Supply
Transmitter Data In Bar
Transmitter Data In
Transmitter Signal Ground


1 (Rx GND)	○
2 (RD+)	N/C
3 (RD-)	
4 (SD)	
5 (Rx Vcc)	
6 (Tx Vcc)	
7 (TD-)	
8 (TD+)	N/C
9 (Tx GND)	○

TOP VIEW

PIN	Symbol	Notes
1	Rx GND	Directly connect this pin to the receiver ground plane
2	RD+	See recommended circuit schematic
3	RD-	See recommended circuit schematic
4	SD	Active high on this indicates a received optical signal
5	Rx Vcc	+3.3V dc power for the receiver section
6	Tx Vcc	+3.3V dc power for the transmitter section
7	TD-	See recommended circuit schematic
8	TD+	See recommended circuit schematic
9	Tx GND	Directly connect this pin to the transmitter ground plane

Professional high-speed optical transceiver

RECOMMENDED CIRCUIT SCHEMATIC




The split-load terminations for ECL signals need to be located at the input of devices receiving those ECL signals. The power supply filtering is required for good EMI performance. Use short tracks from the inductor L1/L2 to the module Rx Vcc and Tx Vcc. A GND plane under the module is required for good EMI and sensitivity performance.

PACKAGE DIAGRAM

Units in mm

1) Pigtail Type




OPN-S8G1314P-40SC / OPN-S8G1314P-40SCI

Note: Length L is 50±3 cm. Other pigtail's length is available upon request.

Professional high-speed optical transceiver

2) Receptacle Type



OPN-S8G1314-40SC / OPN-S8G1314-40SCI

Note: Specifications subject to change without notice.