

Professional high-speed optical transceiver

**OPN-S8G1510T-80SC / OPN-S8G1510T-80SCI / OPN-S8G1510-80SC /
OPN-S8G1510-80SCI / OPN-S8G1510P-80SC / OPN-S8G1510P-80SCI /
OPN-S8G1510TP-80SC / OPN-S8G1510TP-80SCI
1510 nm TX / 1590 nm RX , 3.3V / 1.25 Gb/s RoHS Compliant Single-Fiber Transceiver**

PRODUCT FEATURES

- Single Fiber Bi-Directional Transceiver
 - 1510 nm DFB LD Transmitter
 - 1590 nm Receiver
- 24 dB Link Power Budget At Least
 - Link distance up to 80 km
- Industry Standard 1 x 9 Footprint
 - Single +3.3 V Power Supply
 - RoHS Compliant
- 0 to 70°C Operating: OPN-S8G1315T-80SC
- -50 to 85°C Operating: OPN-S8G1315T-80SCI
 - LVPECL Differential Inputs and Outputs
- LVPECL Signal Detect Output : OPN-S8G1315-80SCI
- LVTTTL Signal Detect Output : OPN-S8G1315T-80SCI
 - Wave Solderable
- Class 1 Laser International Safety Standard IEC-60825Compliant

APPLICATIONS

- WDM 1.25 Gb/s Links
- SONET / SDH Equipment Interconnect
- Fiber Channel 1.063 Gb/s Links

PRODUCT DESCRIPTION

The OPN-S8G1315T-80SCI series are high performance modules for single fiber communications by using 1510 nm transmitter and 1590 nm receiver. The transmitter section uses a multiple quantum well 1510nm DFB laser and is a class 1 laser compliant according to International Safety Standard IEC-60825. The receiver section uses an integrated 1590 nm detector preamplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. A PECL logic interface simplifies interface to external circuitry.

ORDER INFORMATION

P/No.	Bit Rate (Gb/s)	Distance (km)	TX (nm)	RX (nm)	Voltage (V)	Package	Temp. (°C)	TX Power (dBm)	RX Sens. (dBm)	Signal Detect	RoHS Compliant
OPN-S8G1315T-80SC	1.25	80	1510 DFB	1590	3.3	1X9	0 to 70	3 to -2	-26	TTL	Yes
OPN-S8G1315T-80SCI	1.25	80	1510 DFB	1590	3.3	1X9	-50 to 85	3 to -2	-26	TTL	Yes
OPN-S8G1315-80SC	1.25	80	1510 DFB	1590	3.3	1X9	0 to 70	3 to -2	-26	PECL	Yes
OPN-S8G1315-80SCI	1.25	80	1510 DFB	1590	3.3	1X9	-50 to 85	3 to -2	-26	PECL	Yes
OPN-S8G1315P-80SC	1.25	80	1510 DFB	1590	3.3	1X9	0 to 70	3 to -2	-26	PECL	Yes
OPN-S8G1315P-80SCI	1.25	80	1510 DFB	1590	3.3	1X9	-50 to 85	3 to -2	-26	PECL	Yes
OPN-S8G1315TP-80SC	1.25	80	1510 DFB	1590	3.3	1X9	0 to 70	3 to -2	-26	TTL	Yes
OPN-S8G1315TP-80SCI	1.25	80	1510 DFB	1590	3.3	1X9	-50 to 85	3 to -2	-26	TTL	Yes

Professional high-speed optical transceiver

Absolute Maximum Ratings					
Parameter	Symbol	Min	Max	Units	Notes
Storage Temperature	Tstg	-50	85	°C	
Operating Temperature	Topr	0 -50	70 85	°C	OPN-S8G1315T-80SC OPN-S8G1315T-80SCI
Soldering Temperature	---		260	°C	10 seconds on leads only
Power Supply Voltage	Vcc	0	3.6	V	
Input Voltage	---	GND	Vcc	V	
Output Current	Iout	0	30	mA	

Recommended Operating Conditions					
Parameter	Symbol	Min	Typ	Max	Units / Notes
Power Supply Voltage	Vcc	3.13	3.3	3.47	V
Operating Temperature	Topr	0 -50		70 85	°C / OPN-S8G1315T-80SC °C / OPN-S8G1315T-80SCI
Data Rate			1250	1300	Mb/s
Power Supply Current	Icc			280	mA

Transmitter Specifications (0°C < Topr < 70°C, 3.13V < Vcc < 3.47V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Optical Transmit Power	Po	-2	---	3	dBm	1
Output Center Wavelength	λ	1480		1520	nm	
Output Spectrum Width	$\Delta\lambda$	---	---	1	nm	-20 dB Width
Side Mode Suppression Ratio	SMSR	30			dB	
Extinction Ratio	ER	9.0	---	---	dB	
Output Eye	Compliant with IEEE 802.3z					
Optical Rise Time	tr			0.26	ns	20% to 80% Values
Optical Fall Time	tf			0.26	ns	20% to 80% Values
Relative Intensity Noise	RIN			-120	dB/Hz	
Total Jitter	TJ			0.227	ns	2
Electrical						
Data Input Current – Low	I _{IL}	-350			μA	
Data Input Current – High	I _{IH}			350	μA	
Differential Input Voltage	V _{IH} - V _{IL}	300			mV	
Data Input Voltage – Low	V _{IL} - V _{CC}	-2.0		-1.58	V	3
Data Input Voltage -- High	V _{IH} - V _{CC}	-1.1		-0.74	V	3

- Notes: 1. Output power is power coupled into a 9/125 μm single mode fiber.
 2. Measured with a 2⁷-1 PRBS.
 3. These inputs are compatible with 10K, 10KH and 100K ECL and LVPECL inputs.

Professional high-speed optical transceiver

Receiver Specifications (0°C < Topr < 70°C, 3.13V < Vcc < 3.47V)						
Parameter	Symbol	Min	Typ	Max	Units	Notes
Optical						
Sensitivity	---	---	---	-26	dBm	1
Maximum Input Power	Pin	-3		---	dBm	
Signal Detect -- Asserted	Pa	---	---	-26	dBm	Transition: low to high
Signal Detect -- Deasserted	Pd	-40	---	---	dBm	Transition: high to low
Signal detect -- Hysteresis		1.0	---		dB	
Wavelength of Operation		1580	---	1620	nm	2
Optical Return Loss	ORL	14			dB	
Electrical						
Data Output Voltage -- Low	$V_{OL} - V_{CC}$	-2.0		-1.58	V	3
Data Output Voltage -- High	$V_{OH} - V_{CC}$	-1.1		-0.74	V	3
SD Output Voltage -- Low	$V_{OL} - V_{CC}$	-2.0		-1.58	V	OPN-S8G1315-80SCI
SD Output Voltage -- High	$V_{OH} - V_{CC}$	-1.1		-0.74	V	
SD Output Voltage -- Low	V_{OL}	0		0.8	V	OPN-S8G1315T-80SCI
SD Output Voltage -- High	V_{OH}	2.0		$V_{CC} + 0.3$	V	


Notes: 1. Minimum sensitivity and saturation levels at BER=1E-12 for a 2⁷-1 PRBS.

2. At least 30 dB optical isolation for the wavelength 1480 to 1520 nm.

3. These outputs are compatible with 10K, 10KH and 100K ECL and LVPECL outputs.


CONNECTION DIAGRAM

Receiver Signal Ground
Receiver Data Out
Receiver Data Out Bar
Signal Detect
Receiver Power Supply
Transmitter Power Supply
Transmitter Data In Bar
Transmitter Data In
Transmitter Signal Ground



PIN	Symbol	Notes
1	Rx GND	Directly connect this pin to the receiver ground plane
2	RD+	See recommended circuit schematic
3	RD-	See recommended circuit schematic
4	SD	Active high on this indicates a received optical signal
5	Rx Vcc	+3.3V dc power for the receiver section
6	Tx Vcc	+3.3V dc power for the transmitter section
7	TD-	See recommended circuit schematic
8	TD+	See recommended circuit schematic
9	Tx GND	Directly connect this pin to the transmitter ground plane

RECOMMENDED CIRCUIT SCHEMATIC

**Units in mm**

Technical drawing of the SC connector assembly showing front, side, and detail views with dimensions.

Front View (Top):

- Connector pin pitch: $8 \times 2.54 = 20.32$
- Pin diameter: $\phi 0.9$
- PC (SR=20) label
- SC Connector label
- Overall width: 25.30
- Overall length: 39.50
- Overall height: 25.4

Side View (Bottom):

- Overall width: 20.32
- Overall height: 15.8
- Overall depth: 9.3


Detail View (Right):

- Overall length: L
- Overall width: 25.30
- Overall height: 25.4

Note: Length L is 50±3 cm. Other pigtail's length is available upon request.

Professional high-speed optical transceiver

2) Receptacle Type



OPN-S8G1315T-80SC / OPN-S8G1315T-80SCI

Note: Specifications subject to change without notice.